



Cruysberghs
bvba

Chemical

Producer of construction
specialty chemicals

REAXYL®

Approved BASF Construction
Chemicals partner

BASF
The Chemical Company

Dealer of PCI tile adhesive systems and
construction chemical additives

PCI
Voor bouwprofessionals



Reaxyl® CE-45 FL

**Water, dirt and oil repellent
for floors and lintels**

With nanotechnology

Less than 0,1ml absorption after 10 years (according to WTCB)



Cruysberghs Chemical bvba, Heppensesteenweg 56, B- 3945 Ham

Tel.: +32 11 72 71 66 Fax : +32 11 72 71 51

info@cruysberghs.be - www.cruysberghs.be

Description

Reaxyl® CE-45 FL is liquid, ready to use and intended as anti-graffiti, oil and water repellent treatment of various little porous vertical and horizontal surfaces in construction (in- and outside): concrete, masonry, plaster, stones, lintels, floor tiles, limestone, marble, granite, sandstone, slates, reconstructed stone, terracotta, architectural concrete, prefabricated floor stones, self-blocking pavement, etc. Reaxyl® CE-45 FL does not change the look of the surface, it does not form a layer and it lets the material breath. Reaxyl® CE-45 FL is a colourless, water and oil repellent product in watery phase for surface treatment, composed of copolymer and a bridging vinyl resin. Reaxyl® CE-45 FL is suitable for treating floors and other, inside as well as outside.

Use

Reaxyl® CE-45 FL protects against grease and oil. Reaxyl® CE-45 FL has a graffiti repellent, water and oil repellent treatment of walls, floors and facades of private buildings, public buildings and art (tunnels, bridges). Reaxyl® CE-45 FL protects buildings and floors strongly against pollution and dust. Reaxyl® CE-45 FL provides a water and oil base barrier for facades which are exposed to driving rain. Reaxyl® CE-45 FL protects against bad weather conditions, atmospherical influences, sour rain and polluting substances. Reaxyl® CE-45 FL decreases frost damage. Reaxyl® CE-45 FL makes it easier to maintain the surface because of the self-cleaning character of the anti-graffiti product. Reaxyl® CE-45 FL makes it easier to remove chewing gum.

Characteristic

Reaxyl® CE-45 FL is a non-layering system which prevents the danger of peeling because of frost.

Reaxyl® CE-45 FL does not change the look of the surface.

Reaxyl® CE-45 FL lets the material breath – vapour is permeable.

Reaxyl® CE-45 FL is solvent-free, odourless, non-toxic and non-flammable.

Application

Reaxyl® CE-45 FL can be applied to lightly moist surfaces and to new joints (after 3 to 4 days). The surface has to be healthy, cleaned, dusted and degreased. Disinfect the surface: remove moss, lichens and algae with the help of a fungicide of the type Reaxyl® Natri 1216. Repair bad joints, fill in cracks (see PCI joint mortars). Apply until saturation with a brush, a roll or a sprayer (IK Multi 12 BS back sprayer 12), in one or two successive layers (the second layer is to be sprayed on the still wet first layer).

Consumption: Between 0,2 and 1,0 l/m², depending on the porosity of the surface, The surface that was treated with Reaxyl® CE-45 FL can be exposed to rain after +- 2 hours.



Technical information

REAXYL® CE-45 FL

View:

colourless liquid

Material base:

acryl copolymer and a bridging vinyl resin

Viscosity:

100 - 300 mPa.s by 20 °C

Flash point:

no solvents

Active components:

10 %

Aging test:

less than 0,1ml absorption after 10 years.

pH:

7 (neutral)

Vapour diffusion resistance:

< 10 μ

Maximal efficiency:

after 7 days

Drying time:

2 - 5 hours

Processing temperature:

+ 5 to + 30 °C.

Change of the surface tension:

20 – 40mNm

Consumption:

0,2 – 1,0 L/m²

Cleaning after drying:

Reaxyl® ZX-cleaner

Package:

5 and 20 liter

Storage:

1 year cool and dry



Precautions:

- It is strongly recommended to remove the excess product of the surface with a cloth or roll which is lightly moist with water after applying the different layers and before the product dries.
- The temperature of the surface can never be lower than 5°C
- Windows have always to be protected. Incidental stains have to be removed immediately.
- A preceding test on the place of use is always recommended.

Solutions for all your construction problems

webshop

www.cruysberghs.com

 REAXYL®

 TUBE-X™

 BASF
The Chemical Company

 PCI®
Voor bouwprofessionals



Cruysberghs
bvba

Cruysberghs Chemical bvba

Heppensesteenweg 56

3945 Ham - Belgium

Tel: +32 11 72 71 66

Fax: +32 11 72 71 51

E-mail: info@cruysberghs.be

Website: www.cruysberghs.be

© 2018 Cruysberghs Chemical bvba - All rights reserved. All images are property of Cruysberghs Chemical bvba. The logos of BASF and PCI are property of BASF Chemical Company. All information distributed through this document is for information purposes only, without adverse recognition, nor any other warranty than those resulting from the sale of our products, within the bounds of our terms and conditions. Users must always consult our last published technical data sheets; a copy of which is available upon request. The information indicated above is the result of a thorough study, previous data are hereby invalid. Test this product yourself and test whether it is satisfactory for your goals. We are not responsible for any misuse of our products or damage, nor do we guarantee if our products were not suitable for your particular purposes. Nobody has the right to give guarantees or guidelines in our name about this product, that are beyond the contents of this information sheet.