

DECLARATION OF PERFORMANCE

DE0029/02

PCI[®]
Für Bau-Profis

Unique identification code of the product-type:

Augsburg, 30.03.2016

PCI Durapox[®] NT plus (DE0029/02)

Intended use/es:

EN 12004 R2T

Improved reaction resin adhesive with reduced slip for tiles for indoor and outdoor use

Manufacturer:

PCI Augsburg GmbH, Piccardstraße 11, D-86159 Augsburg

System/s of AVCP:

System 3, System 4 (Reaction to fire)

Harmonised standard / Notified body/ies:

EN 12004:2007+A1:2012

Säurefliesner-Vereinigung e.V. Institut für Wand- und Bodenbeläge (NB 1212)

Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 4	EN 12004:2007+A1:2012
Initial shear adhesion strength	≥ 2,0 N/mm ²	System 3	
Shear adhesion strength after thermal shock	≥ 2,0 N/mm ²		
Shear adhesion strength after water immersion	≥ 2,0 N/mm ²		
Dangerous substances	NPD		

Specific Technical Documentation: 644/14

Performance without further testing: Reaction to fire: Class E
Fulfilled requirements: Organic content: < 50 % in weight
Maximum layer thickness: 5 mm

The performance of the product identified above is in conformity with the set of declared performance/s.
This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011 and No 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



.....
Marc Köppe
managing director



.....
Manfred Grundmann
managing director