

DECLARATION OF PERFORMANCE

DE0085/03

PCI[®]
Für Bau-Profis

Unique identification code of the product-type:

Augsburg, 21.02.2017

PCI FT[®] Extra (DE0085/03)

Intended use/es:

EN 12004 C2TE S1

Improved deformable cementitious adhesive with reduced slip and extended open time for tiles for indoor and outdoor use

Manufacturer:

PCI Augsburg GmbH, Piccardstraße 11, D-86159 Augsburg

System/s of AVCP:

System 3, System 3 (Reaction to fire)

Harmonised standard / Notified body/ies:

**EN 12004:2007+A1:2012
TÜV Rheinland LGA Bautechnik GmbH (NB 0780)
MPA Dresden GmbH (NB 0767)**

Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class A1, A1fl	System 3	EN 12004:2007+A1:2012
Early tensile adhesion strength	NPD	System 3	
Initial tensile adhesion strength	≥ 1,0 N/mm ²		
Tensile adhesion strength after water immersion	≥ 1,0 N/mm ²		
Tensile adhesion strength after heat ageing	≥ 1,0 N/mm ²		
Tensile adhesion strength after freeze/thaw cycle	≥ 1,0 N/mm ²		
Dangerous substances	NPD		


The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011 and No 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



.....
Marc C. Köppe
managing director



.....
Frank Rösiger
managing director