

DECLARATION OF PERFORMANCE

DE0061/03

PCI[®]

Für Bau-Profis

Unique identification code of the product-type:

Augsburg, 02.03.2017

PCI Polyfix[®] 5 Min. (DE0061/03)

Intended use/es:

EN 998-1 GP CS IV

General purpose rendering mortar

Manufacturer:

PCI Augsburg GmbH, Piccardstraße 11, D-86159 Augsburg

System/s of AVCP:

System 4, System 4 (Reaction to fire)

Harmonised standard / Notified body/ies:

EN 998-1:2016

Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class A1	System 4	EN 998-1:2016
Water absorption	W0	System 4	
Water vapour permeability μ	≤ 25		
Adhesion	$\geq 1,0 \text{ N/mm}^2$ - FP:A/B		
Thermal conductivity $\lambda_{10,\text{dry}}$ (Table value to EN 1745:2012)	$\leq 1,11 \text{ W/(m}\cdot\text{K)}$ for P=50% $\leq 1,21 \text{ W/(m}\cdot\text{K)}$ for P=90%		
Durability	NPD		
Dangerous substances	NPD		

Specific Technical Documentation: 478/15
Performance without further testing: Reaction to fire: Class A1
Fulfilled requirements: Organic content: < 1 % in weight


The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011 and No 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



.....
Marc C. Köppe
managing director



.....
Frank Rösiger
managing director