

DECLARATION OF PERFORMANCE

DE0417/03

PCI[®]
Für Bau-Profis

Unique identification code of the product-type:

Augsburg, 24.10.2017

PCI Adaptol® (DE0417/03)

Intended use/es:

EN 15651-1 Type F EXT-INT

Sealants for non-structural use in joints in buildings and pedestrian walkways

Sealants for facade elements, Class F 7,5P

Conditioning: Method A

Substrate: Mortar, Aluminium

Manufacturer:

PCI Augsburg GmbH, Piccardstraße 11, D-86159 Augsburg

System/s of AVCP:

System 3, System 3 (Reaction to fire)

Harmonised standard / Notified body/ies:

EN 15651-1:2012

GINGER CEBTP (NB 0074)

Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	Evaluated	System 3	
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 25 %		
Tensile properties after immersion in water at 23 °C	≥ 25 %		
Durability	Pass		

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011 and No 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Marc C. Köppe
managing director



Frank Rösiger
managing director