

Cruysberghs
bvba
Chemical

Producer of construction
specialty chemicals **REAXYL**[®]

Approved BASF Construction
Chemicals partner



Dealer of PCI tile adhesive systems and
construction chemical additives



Reaxyl[®] Tmax 350

Self-levelling elastic waterproof pouring sealant
Without primer



Cruysberghs Chemical bvba, Heppensesteenweg 56, B- 3945 Ham
Tel.: +32 11 72 71 66 Fax.: +32 11 72 71 51
info@cruysberghs.be - www.cruysberghs.be



Application

Reaxyl® Tmax 350 is a self-levelling, permanent elastic, waterproof pouring sealant.

Reaxyl® Tmax 350 makes all horizontal movement joints, dummy joints and expansion joint permanently elastic waterproof.

Reaxyl® Tmax 350 has an excellent adhesion without primer.

Reaxyl® Tmax 350 can be immediately covered with **Reaxyl® Rubar® Color PG** if required.





Instructions

Do not stir, mix or dilute **Reaxyl® Tmax 350**. It is ready to use.

Fill out big holes first with **Reaxyl® Tubefix 2K PU RPD**. By groundwater first fill out the leak with Masterseal 590 (ask advise).

Apply **Reaxyl® Tmax 350** with a piping bag on a dust-free and cleaned surface. You can dry the joint with a hairdryer or another tool (hot air gun). If required, taped with masking tape.

Reaxyl® Tmax 350 can immediately be covered with **Reaxyl® Rubar® Color PG**.

Reaxyl® Tmax 350 can be applied to a light moist surface, is UV-stable and instantly rainproof.

Technical information

Material base: polyether prepolymer (bitumen-free)

Solvent: solvent-free, do not dilute, do not stir, do not mix!

Flash point: irrelevant

Density: 1,4 gr/cm³.

Shore A hardness: 25

Vapour diffusion resistance: $\mu = 4291$

UV resistant

Stretch until break: 350%

Pulling strength: 0,95 N/mm²

Viscosity: 400 mPa.s.

Drying time: ½ – 5 hours depending on the temperature and the humidity.

Color: gray (can be sanded in the required colour)

Rainproof: immediate


Only apply to positive waterside.

Consumption: 1,4k/l joint content

Processing temperature: +5 to +40°C

Storage: 1 year, cool and dry

Package: 1,5 kg and 14 kg



Solutions for all your construction problems

webshop

www.cruysbergghs.com



Cruysbergghs

bvba

Chemical

Cruysbergghs Chemical bvba
Heppensesteenweg 56
3945 Ham - Belgium
Tel: +32 11 72 71 66
Fax: +32 11 72 71 51
E-mail: info@cruysbergghs.be
Website: www.cruysbergghs.be

© 2018 Cruysbergghs Chemical bvba - All rights reserved. All images are property of Cruysbergghs Chemical bvba. The logos of BASF and PCI are property of BASF Chemical Company. All information distributed through this document is for information purposes only, without adverse recognition, nor any other warranty than those resulting from the sale of our products, within the bounds of our terms and conditions. Users must always consult our last published technical data sheets; a copy of which is available upon request. The information indicated above is the result of a thorough study, previous data are hereby invalid. Test this product yourself and test whether it is satisfactory for your goals. We are not responsible for any misuse of our products or damage, nor do we guarantee if our products were not suitable for your particular purposes. Nobody has the right to give guarantees or guidelines in our name about this product, that are beyond the contents of this information sheet.